

12" | 12NPM

Mid-woofer



Key features:

- CARBON FIBER LOADED PAPER CONE
- VERY HIGH EFFICIENCY
- LIGHTWEIGHT MECHANICAL STRUCTURE

Design notes:

The 12NPM is a high efficiency, (98 dB 1watt / 1 meter) 12-inch mid bass woofer with incredibly linear frequency response characteristics, extreme high power handling capability while generating low harmonic distortion artifacts.- The 12NPM uses a lightweight carbon fiber loaded cone assembly along with a precision double roll constant geometry surround. This combination provides remarkable strength, high efficiency and a excursion

linearity of 18.2mm.

Magnetic Circuit
REDCATT engineers have developed a lightweight, inside-neodymium slug based magnetic circuit capable of delivering the highest level of performance providing a consistent, high integrity magnetic flux gap, ultra low distortion characteristic and high efficiency cooling system. The magnetic circuit design is optimized to generate the

minimum amount of flux modulation, providing exceptional stability.

Specifications:

General specs

Nominal Diameter: 12"
Rated Impedance: 8 ohm

Power handling

AES Power: 450 watts
Program Power: 900 watts
Peak Power: 1800 watts

Voice Coil

Diameter: 3 in.
Winding wire: CCAW
Former: Glass Fiber
Winding height: 18.6 mm

T/S Parameters

Resonant frequency: 49 Hz
Re: 4.7 ohm
Qes: 0.32
Qms: 9.95
Qts: 0.31
Vas: 63.6 liters
Sd: 531 cm²
Sensitivity: 98 dB
Mms: 65.6 grams
Bl: 17.3
Le: 0.65 mH

Design details

Surround Material: Fabric
Cone material: Paper
Spider: Nomex
Plate thickness: 11 mm
Peak to peak linear cone displacement: 18.2 mm
Overall diameter: 315 mm
Bolt circle diameter: 298 mm
Baffle cutout dia.: 285 mm
Number of mounting holes: 8
Depth (flange to rear): 142.5 mm
Net weight: 4.1kg


Ordering codes:

12NPM-X8 ohm-054

Recone kits:
RC12NPMX-054

In many cases REDCATT produces 4 ohms, 8 ohms and 16 ohms versions. Indicate what impedance do you need in your request.

Frequency response & Impedance



Frequency response measured on IAC baffle

2D drawing

